NSN 5930-00-504-6584

Rotary Switch - Page 1 of 2



Trotally Switch Tage 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-504-6584
Thread Class:
2a single mounting facility
Thread Length:
0.375 inches single mounting facility
Overall Length:
3.491 inches
Overall Height:
1.484 inches
Overall Width:
1.438 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
2.250 inches single actuator
Nonturn Device Radius:
0.438 inches at 9: 00 o'clock
Individual Section Quantity:
2
Knob Manufacturer Code:
71590
Knob Manufacturer Part Number:
P-120
Nonturn Device Type:
Tab at 9: 00 o'clock
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
3 each section rear
Throw Quantity:
5 each section rear
Mounting Method:
Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

6.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

NSN 5930-00-504-6584Rotary Switch - Page 2 of 2



Terminal Type:	
Tab, solder lug	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
30.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Adjustable stop single actuator	
Contact Load Current Rating:	
5.5 amperes resistive load highest dc voltage rating at sea level	
Style Designator:	
Circular wafer, bushing mount	
Thread Series Designator:	
Unef single mounting facility	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A052b0	