## NSN 5930-00-504-6674

Sensitive Switch - Page 1 of 2

Body Style:
Hole mounted
Actuator Style:

0.156 inches

**Actuator Diameter:** 

Round



View Online at https://aerobasegroup.com/nsn/5930-00-504-6674

Actuator Free Position Height: 0.513 inches Housing Height: 1.312 inches Housing Length: 2.125 inches Housing Width: 0.875 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches Maximum Voltage Rating In Volts: 125.0 ac End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit Switch Release Force: Between 3.0 ounces and 4.0 ounces Criticality Code Justification: Feat Switch Actuating Force: Between 12.0 ounces and 14.0 ounces Actuator Movement: 0.062 overtravel inches and 0.001 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Special Features: Weapon system essential Terminal Type And Quantity:
Housing Height:  1.312 inches  Housing Length:  2.125 inches  Housing Width:  0.875 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Width:  1.375 inches  Maximum Voltage Rating In Volts:  125.0 ac  End Application:  Radar set, firefinder (an/tpq-36).  Inclosure Type:  Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Housing Height:  1.312 inches  Housing Length: 2.125 inches  Housing Width: 0.875 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches  Maximum Voltage Rating In Volts: 125.0 ac  End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit  Switch Release Force: Between 3.0 ounces and 4.0 ounces  Criticality Code Justification: Feat  Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features: Weapon system essential
1.312 inches Housing Length: 2.125 inches Housing Width: 0.875 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches Maximum Voltage Rating In Volts: 125.0 ac End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit Switch Release Force: Between 3.0 ounces and 4.0 ounces Criticality Code Justification: Feat Switch Actuating Force: Between 12.0 ounces and 14.0 ounces Actuator Movement: 0.062 overtravel inches and 0.001 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Special Features: Weapon system essential
Housing Length: 2.125 inches Housing Width: 0.875 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches Maximum Voltage Rating In Volts: 125.0 ac End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit Switch Release Force: Between 3.0 ounces and 4.0 ounces Criticality Code Justification: Feat Switch Actuating Force: Between 12.0 ounces and 14.0 ounces Actuator Movement: 0.062 overtravel inches and 0.001 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Special Features: Weapon system essential
2.125 inches  Housing Width: 0.875 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches  Maximum Voltage Rating In Volts: 125.0 ac  End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit  Switch Release Force: Between 3.0 ounces and 4.0 ounces  Criticality Code Justification: Feat  Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features: Weapon system essential
Housing Width:  0.875 inches  Center To Center Distance Between Housing Mounting Facilities Parallel To Width:  1.375 inches  Maximum Voltage Rating In Volts:  125.0 ac  End Application:  Radar set, firefinder (an/tpq-36).  Inclosure Type:  Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches  Maximum Voltage Rating In Volts: 125.0 ac  End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit  Switch Release Force: Between 3.0 ounces and 4.0 ounces  Criticality Code Justification: Feat  Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features:  Weapon system essential
Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.375 inches  Maximum Voltage Rating In Volts: 125.0 ac  End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit  Switch Release Force: Between 3.0 ounces and 4.0 ounces  Criticality Code Justification: Feat  Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features:  Weapon system essential
1.375 inches  Maximum Voltage Rating In Volts: 125.0 ac  End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit  Switch Release Force: Between 3.0 ounces and 4.0 ounces  Criticality Code Justification: Feat  Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features: Weapon system essential
Maximum Voltage Rating In Volts:  125.0 ac  End Application:  Radar set, firefinder (an/tpq-36).  Inclosure Type:  Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit Switch Release Force: Between 3.0 ounces and 4.0 ounces Criticality Code Justification: Feat Switch Actuating Force: Between 12.0 ounces and 14.0 ounces Actuator Movement: 0.062 overtravel inches and 0.001 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Special Features: Weapon system essential
End Application: Radar set, firefinder (an/tpq-36). Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit Switch Release Force: Between 3.0 ounces and 4.0 ounces Criticality Code Justification: Feat Switch Actuating Force: Between 12.0 ounces and 14.0 ounces Actuator Movement: 0.062 overtravel inches and 0.001 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Special Features: Weapon system essential
Radar set, firefinder (an/tpq-36).  Inclosure Type:  Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained single switch unit Switch Release Force: Between 3.0 ounces and 4.0 ounces Criticality Code Justification: Feat Switch Actuating Force: Between 12.0 ounces and 14.0 ounces Actuator Movement: 0.062 overtravel inches and 0.001 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Special Features: Weapon system essential
Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Nonpile-up Contact Arrangement:  1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
1 pole, single throw, both positions maintained single switch unit  Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Switch Release Force:  Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Between 3.0 ounces and 4.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Criticality Code Justification: Feat  Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features:  Weapon system essential
Switch Actuating Force: Between 12.0 ounces and 14.0 ounces  Actuator Movement: 0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac  Special Features:  Weapon system essential
Switch Actuating Force:  Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Between 12.0 ounces and 14.0 ounces  Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Actuator Movement:  0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
0.062 overtravel inches and 0.001 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
Contact Load Current Rating At Maximum Rated Voltage:  10.000 amperes resistive ac  Special Features:  Weapon system essential
10.000 amperes resistive ac  Special Features:  Weapon system essential
Special Features: Weapon system essential
Weapon system essential
• •
Terminal Type And Quantity:
2 wire lead
Shelf Life:

## NSN 5930-00-504-6674

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0