

View Online at <https://aerobasegroup.com/nsn/5930-00-504-7077>

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

1.960 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Overall Height:**

2.180 inches

**Overall Width:**

0.695 inches

**Bushing Length:**

0.590 inches

**Body Length:**

1.960 inches

**Body Width:**

0.695 inches

**Body Height:**

0.930 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.240 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.320 inches

**Actuator Height:**

0.410 inches

**Actuator Free Position Height:**

1.000 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

Between 0.065 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0