## NSN 5930-00-504-7131

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-504-7131

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.875 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.830 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.045 inches
Actuator Free Position Height:
0.625 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

28.0 ounces

## NSN 5930-00-504-7131

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	am.	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0