

View Online at <https://aerobasegroup.com/nsn/5930-00-504-7147>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

0.875 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.840 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.035 inches

Actuator Free Position Height:

0.625 inches

Maximum Voltage Rating In Volts:

460.0 ac

End Application:

Fnimitz class cvn, forrestal class cv, kidd class ddg, emory s. Land class as, wasp class lhd, los angeles class ssn (688), virginia class cgn (41), sturgeon class ssn (637), spruance class dd (963).

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

9.0 ounces

Actuator Movement:

Between 0.012 pretravel inches and 0.005 overtravel inches and 0.0003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0