

View Online at <https://aerobasegroup.com/nsn/5930-00-504-7147>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.940 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.687 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

0.840 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.094 inches

**Actuator Height:**

0.035 inches

**Actuator Free Position Height:**

0.625 inches

**Maximum Voltage Rating In Volts:**

460.0 ac

**End Application:**

Fnimitz class cvn, forrestal class cv, kidd class ddg, emory s. Land class as, wasp class lhd, los angeles class ssn (688), virginia class cgn (41), sturgeon class ssn (637), spruance class dd (963).

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

9.0 ounces

**Actuator Movement:**

Between 0.012 pretravel inches and 0.005 overtravel inches and 0.0003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0