# NSN 5930-00-504-8127

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-504-8127

#### **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

3.000 inches

## **Overall Height:**

2.828 inches

#### **Overall Width:**

2.828 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.938 inches single actuator

#### **Unthreaded Mounting Hole Diameter:**

## 0.190 inches single mounting facility

## Individual Section Quantity:

4

#### Knob Manufacturer Code:

80064

# Knob Manufacturer Part Number:

9s5401l1

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 each section rear

## **Throw Quantity:**

2 each section rear

## Mounting Facility Circle Radius:

1.156 inches single mounting facility

## **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### Features Provided:

Actuator knob

## Thready Qty Per Inch (tpi):

24 single mounting facility

## **Thread Size:**

0.190 inches single mounting facility

## **Contact Voltage Rating In Volts:**

120.0 ac at sea level

## Mounting Facility Pattern:

Four position circular single mounting facility

# NSN 5930-00-504-8127

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load ac at sea level

#### **Special Features:**

Round threaded hole shaft

## Style Designator:

Tap, circuit selector

# Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A052b0