## NSN 5930-00-504-8671

Sensitive Switch - Page 1 of 2

Body Style: Hole mounted Overall Length: 0.781 inches



View Online at https://aerobasegroup.com/nsn/5930-00-504-8671

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Between 0.373 inches and 0.377 inches
Overall Height:
0.489 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Round
Actuator Free Position Height:
0.296 inches
Maximum Voltage Rating In Volts:
240.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
12.0 ounces
Actuator Movement:
Between 0.008 pretravel inches and 0.005 overtravel inches and 0.0015 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug

## NSN 5930-00-504-8671

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0