# NSN 5930-00-504-8671

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-504-8671

## **Body Style:**

Hole mounted

#### **Overall Length:**

0.781 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

### **Overall Height:**

0.489 inches

**Overall Width:** 

0.250 inches

**Body Length:** 

0.781 inches

#### Body Width:

0.250 inches

#### **Case Material:**

Plastic

# **Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

### **Actuator Free Position Height:**

0.296 inches

### Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

### Inclosure Type:

Fully enclosed

### **Mounting Method:**

Unthreaded hole

### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

2.0 ounces

### Switch Actuating Force:

12.0 ounces

### **Actuator Movement:**

Between 0.008 pretravel inches and 0.005 overtravel inches and 0.0015 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

# **Precious Material And Location:**

Contacts silver

## **Terminal Type And Quantity:**

3 tab, solder lug

# NSN 5930-00-504-8671

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

