

View Online at <https://aerobasegroup.com/nsn/5930-00-504-9357>

**Thread Length:**

0.500 inches all threaded stud

**Overall Length:**

3.370 inches

**Body Diameter:**

1.720 inches

**Body Length:**

2.250 inches

**Overall Diameter:**

2.125 inches

**Distance Between Mounting Facility Centers:**

1.250 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Threaded stud

**Features Provided:**

Electrical box connector

**Thready Qty Per Inch (tpi):**

32 all threaded stud

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.190 inches all threaded stud

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

500.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

2.00 actuation point pounds per square inch and 1.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

24.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf all threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0