

View Online at <https://aerobasegroup.com/nsn/5930-00-504-9357>

Thread Length:

0.500 inches all threaded stud

Overall Length:

3.370 inches

Body Diameter:

1.720 inches

Body Length:

2.250 inches

Overall Diameter:

2.125 inches

Distance Between Mounting Facility Centers:

1.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Threaded stud

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches all threaded stud

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2.00 actuation point pounds per square inch and 1.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0