

View Online at <https://aerobasegroup.com/nsn/5930-00-504-9964>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

4.562 inches

Overall Height:

1.437 inches

Overall Width:

1.578 inches

Body Length:

3.562 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Temperature Sensing Element Type:

Expanding shell

Mounting Facility Circle Radius:

0.625 inches

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 650.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00 to 650.00 actuation point degrees fahrenheit and -100.00 to 650.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

120.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0