

View Online at <https://aerobasegroup.com/nsn/5930-00-505-4380>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Length:

1.750 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.250 inches

Housing Height:

1.250 inches

Housing Length:

2.500 inches

Housing Width:

1.218 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.563 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.875 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

480.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 4.0 pretravel degrees and 8.0 overtravel degrees and 1.5 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes inductive ac

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0