NSN 5930-00-505-8877

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-505-8877

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Style:
Round
Actuator Diameter:
Between 0.243 inches and 0.248 inches
Actuator Height:
Between 0.849 inches and 0.869 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 118.0 pretravel degrees and 100.0 overtravel degrees and 10.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
25.000 amperes resistive dc and 10.000 amperes inductive dc
Special Features:
Actuator on right hand side
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a

NSN 5930-00-505-8877

Sensitive Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0