## NSN 5930-00-506-1922

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-506-1922

Hazardous Locations/environmental Protection:
Dustproof
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.125 inches
Housing Height:
1.125 inches
Housing Length:
2.000 inches
Housing Width:
1.156 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.375 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
reatures Frontieu.
Actuator seal
Actuator seal
Actuator seal  Nonpile-up Contact Arrangement:
Actuator seal  Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit
Actuator seal  Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force:
Actuator seal  Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force:  64.0 ounces
Actuator seal  Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force:  64.0 ounces  Actuator Movement:
Actuator seal  Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force:  64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches
Actuator seal  Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force:  64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force:  64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 connector, receptacle
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity: 4 connector, receptacle  Shelf Life:
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 connector, receptacle  Shelf Life:  N/a
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 connector, receptacle  Shelf Life:  N/a
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity: 4 connector, receptacle  Shelf Life:  N/a  Unit Of Measure:
Nonpile-up Contact Arrangement:  1 two circuit, double break/double make, one position momentary single switch unit  Switch Actuating Force: 64.0 ounces  Actuator Movement:  Between 0.100 pretravel inches and 0.125 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac  Terminal Type And Quantity: 4 connector, receptacle  Shelf Life: N/a  Unit Of Measure:  Demilitarization: