

View Online at <https://aerobasegroup.com/nsn/5930-00-506-4478>

**Thread Length:**

0.375 inches single mounting facility and 0.380 inches single mounting facility

**Overall Length:**

Between 2.745 inches and 3.000 inches

**Overall Height:**

Between 1.870 inches and 1.880 inches

**Overall Width:**

Between 1.620 inches and 1.630 inches

**First Flat Length:**

0.370 inches single actuator and 0.380 inches single actuator

**Flat Height:**

0.213 inches single actuator and 0.223 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.870 inches single actuator and 0.880 inches single actuator

**Nonturn Device Radius:**

0.526 inches at 10:00 o'clock and 0.536 inches at 10:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 10:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 1st section front

**Throw Quantity:**

5 2nd section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Shaft Flat/slot Angular Location:**

165.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0