

View Online at <https://aerobasegroup.com/nsn/5930-00-506-4478>

Thread Length:

0.375 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

Between 2.745 inches and 3.000 inches

Overall Height:

Between 1.870 inches and 1.880 inches

Overall Width:

Between 1.620 inches and 1.630 inches

First Flat Length:

0.370 inches single actuator and 0.380 inches single actuator

Flat Height:

0.213 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.870 inches single actuator and 0.880 inches single actuator

Nonturn Device Radius:

0.526 inches at 10: 00 o'clock and 0.536 inches at 10: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 10: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 1st section front

Throw Quantity:

5 2nd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Shaft Flat/slot Angular Location:

165.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0