

View Online at <https://aerobasegroup.com/nsn/5930-00-506-6885>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Body Diameter:**

1.000 inches

**Bushing Length:**

Between 1.700 inches and 1.900 inches

**Body Length:**

0.980 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

1.050 inches

**Actuator Free Position Height:**

1.050 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.860 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 4.000 amperes motor ac

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0