

View Online at <https://aerobasegroup.com/nsn/5930-00-506-6968>

Thread Class:

2b all threaded hole

Overall Length:

5.656 inches

Overall Height:

4.062 inches

Overall Width:

2.297 inches

Body Height:

3.250 inches

Longest Horizontal Distance Between Mounting Centers:

1.453 inches

Intermediate Horizontal Distance Between Mounting Centers:

1.453 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Features Provided:

Capillary tube end seal connection

Contact Action Stimulus:

Increase

Proof Pressure:

325.00 pounds per square inch

Thread Size:

0.190 inches all threaded hole

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+8.00/+70.00 actuation point pounds per square inch gage and +8.00/+70.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

24.0 dc at sea level second voltage

Special Features:

Operates on a 120.0 second time delay

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0