

View Online at <https://aerobasegroup.com/nsn/5930-00-506-6968>

**Thread Class:**

2b all threaded hole

**Overall Length:**

5.656 inches

**Overall Height:**

4.062 inches

**Overall Width:**

2.297 inches

**Body Height:**

3.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.453 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

1.453 inches

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Base and threaded hole

**Features Provided:**

Capillary tube end seal connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

325.00 pounds per square inch

**Thread Size:**

0.190 inches all threaded hole

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+8.00/+70.00 actuation point pounds per square inch gage and +8.00/+70.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

24.0 dc at sea level second voltage

**Special Features:**

Operates on a 120.0 second time delay

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0