

View Online at <https://aerobasegroup.com/nsn/5930-00-508-0029>

**Body Style:**

Hole mounted

**Overall Length:**

0.780 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

1.120 inches

**Overall Width:**

0.390 inches

**Body Length:**

0.780 inches

**Body Width:**

0.330 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.150 inches

**Actuator Height:**

0.090 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

0.370 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 3.300 amperes motor ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0