

View Online at <https://aerobasegroup.com/nsn/5930-00-508-0092>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

1.250 inches

**Overall Height:**

0.440 inches

**Overall Width:**

0.401 inches

**Mounting Slot Width:**

0.125 inches

**Body Length:**

0.776 inches

**Body Width:**

0.401 inches

**Body Height:**

0.251 inches

**Distance Between Mounting Facility Centers:**

1.000 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -85.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Mounting Method:**

Clip and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.5 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

-20.00/+200.00 actuation point degrees fahrenheit and -20.00/+200.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

104.00 actuation point degrees fahrenheit and 99.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0