

View Online at <https://aerobasegroup.com/nsn/5930-00-508-0104>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Width Between Flats:**

0.062 inches single actuator

**Overall Length:**

1.194 inches

**First Flat Length:**

0.250 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.344 inches single actuator

**Overall Diameter:**

1.156 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

4 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

50.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0