# NSN 5930-00-508-0104

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-508-0104

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.250 inches single mounting facility

## Width Between Flats:

0.062 inches single actuator

#### **Overall Length:**

1.194 inches

#### First Flat Length:

0.250 inches single actuator

#### Shaft Diameter:

0.125 inches single actuator

### Shaft Length:

0.344 inches single actuator

### **Overall Diameter:**

1.156 inches

### Individual Section Quantity:

1

### Switch Contact Basic Design:

Nonpile-up symmetrical

### **Pole Quantity:**

1 single section rear

### Throw Quantity:

4 single section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.250 inches single mounting facility

### **Contact Voltage Rating In Volts:**

50.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

4 single actuator

### Shaft Type:

Round, parallel flatted single actuator

## **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Makes before breaks single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-508-0104

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0