## NSN 5930-00-509-6184

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-509-6184

Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
2.000 inches
Overall Width:
2.000 inches
Individual Section Quantity:
2
Nonturn Device Type:
Tab at 6: 00 o'clock
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
4 each section front
Mounting Method:
Threaded bushing single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## **NSN 5930-00-509-6184**Rotary Switch - Page 2 of 2



Fiig:

A052b0