NSN 5930-00-509-8653

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-509-8653 **Thread Class:** 2b single mounting facility **Overall Length: 4.312 inches Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section front **Throw Quantity:** 3 each section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

NSN 5930-00-509-8653

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0