# NSN 5930-00-513-0976

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-513-0976

#### **Thread Class:**

2b single mounting facility

#### Hazardous Locations/environmental Protection:

Explosion proof

## **Overall Length:**

3.125 inches

#### **Overall Height:**

2.500 inches

#### **Overall Width:**

2.500 inches

#### Flat Height:

0.218 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Individual Section Quantity:

1

## Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

А

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 single section front

#### **Throw Quantity:**

1 single section front

## Mounting Facility Circle Radius:

0.840 inches single mounting facility

#### **Mounting Method:**

Threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

#### Thready Qty Per Inch (tpi):

24 single mounting facility

### Thread Size:

0.250 inches single mounting facility

## **Contact Voltage Rating In Volts:**

125.0 ac at sea level

## Switch Actuator Momentary Position:

Clockwise single actuator

# NSN 5930-00-513-0976

Rotary Switch - Page 2 of 2



Shaft Flat/slot Angular Location: 180.0 degrees from contact position 1 single actuator Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Switch Actuator Positioning Increment:** 45.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level Style Designator: Tap, circuit selector **Thread Series Designator:** Uns single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0