

View Online at <https://aerobasegroup.com/nsn/5930-00-513-2841>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

Between 0.568 inches and 0.628 inches

**Overall Diameter:**

Between 0.288 inches and 0.308 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

10 single section rear

**Mounting Method:**

Printed circuit single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

100.0 milliamperes resistive load dc at sea level

**Special Features:**

Incl screw driver slot 0.020 in. W by 0.125 in. Lg

**Style Designator:**

Miniature, pin mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0