

View Online at <https://aerobasegroup.com/nsn/5930-00-513-3418>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

Between 0.770 inches and 0.790 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.346 inches and 0.366 inches

**Unthreaded Mounting Hole Diameter:**

0.086 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.046 inches

**Actuator Height:**

0.070 inches

**Actuator Free Position Height:**

0.360 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

11.000 amperes resistive ac

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0