NSN 5930-00-515-2746

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-515-2746

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
4.750 inches
Overall Height:
2.938 inches
Overall Width:
2.813 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
1 single section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Contact Owntoning Action

Breaks before makes single section front

NSN 5930-00-515-2746

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0