

View Online at <https://aerobasegroup.com/nsn/5930-00-515-3578>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.088 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.095 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.875 inches single actuator

Overall Diameter:

0.719 inches

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

150.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

25.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0