NSN 5930-00-518-0752

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-518-0752

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.950 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
1.026 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
End Application:
Shipboard material handling equipment (mhe), circuit switch, an/tyc-39, los angeles class ssn (688), forrestal class cv, virginia class cgn
(41), sturgeon class ssn (637), ticonderoga class cg (47), radar, series an/sps-49 (v), spruance class dd (963)
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
1.5 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
6.0 inch-ounces
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Special Features:
Weapon system essential
Terminal Type And Quantity:
3 tab, solder lug

N/a

Shelf Life:

NSN 5930-00-518-0752

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0