

View Online at <https://aerobasegroup.com/nsn/5930-00-518-0752>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.950 inches

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Length:

1.026 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.150 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Shipboard material handling equipment (mhe), circuit switch, an/tyc-39, los angeles class ssn (688), forrestal class cv, virginia class cgn (41), sturgeon class ssn (637), ticonderoga class cg (47), radar, series an/sps-49 (v), spruance class dd (963)

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.5 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

6.0 inch-ounces

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0