## NSN 5930-00-518-0846

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-518-0846

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus proof and moisture proof
Overall Length:
5.312 inches
Overall Height:
2.562 inches
Overall Width:
2.625 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Height:
0.687 inches
Actuator Free Position Height:
1.593 inches
Housing Height:
2.562 inches
Housing Length:
5.312 inches
Housing Width:
2.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
440.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Bracket and unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
16.0 ounces
Switch Actuating Force:
336.0 ounces
Actuator Movement:

5.0 pretravel degrees and 27.0 overtravel degrees and 4.0 differential degrees

## NSN 5930-00-518-0846

Sensitive Switch - Page 2 of 2



Contact Load Curren	t Rating	At Maximum	Rated	Voltage:
---------------------	----------	------------	-------	----------

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

4 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0