

View Online at <https://aerobasegroup.com/nsn/5930-00-518-4605>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.287 inches and 0.307 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.349 inches and 0.369 inches

**Actuator Style:**

Round

**Actuator Height:**

0.030 inches

**Actuator Free Position Height:**

Between 0.315 inches and 0.345 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 5.000 amperes resistive ac

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0