

View Online at <https://aerobasegroup.com/nsn/5930-00-519-0294>

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Longest Vertical Distance Between Mounting Centers:**

2.875 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Base

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

575.00 pounds per square inch

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+50.00/+500.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point hex nut

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Frequency In Hertz:**

60.0 single voltage

**Reference Number Differentiating Characteristics:**

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0