NSN 5930-00-519-3287

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-519-3287

Maximum Voltage Rating In Volts: 230.0 ac and 24.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch uncontact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	
230.0 ac and 24.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch uncontact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch ur Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch uncontact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Thready Qty Per Inch (tpi): 32 Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch unce Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ace Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch ur Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Thread Size: 0.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch un Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
O.500 inches Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch un Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action single switch un Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
1 pole, single throw, normally open, momentary action single switch un Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Contact Load Current Rating At Maximum Rated Voltage: 17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
17.000 amperes resistive dc and 7.500 amperes resistive ac Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	it
Thread Series Designator: Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Un Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	
2 tab, solder lug Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A053a0	