## **NSN 5930-00-519-4779** Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-519-4779
Thread Class:
2b single threaded hole
Overall Length:
4.844 inches
Overall Height:
1.530 inches
Overall Width:
1.190 inches
Body Length:
2.000 inches
Mounting Method:
Threaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Thread Size:
0.190 inches single threaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
785.00 actuation point feet per minute and 735.00 actuation point feet per minute and 750.00 actuation point feet per minute and 700.00
deactuation point feet per minute and 630.00 deactuation point feet per minute and 615.00 deactuation point feet per minute and 85.00
differential point feet per minute and 105.00 differential point feet per minute and 135.00 differential point feet per minute
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf single threaded hole
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5930-00-519-4779

Flow Switch - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A048b0