

View Online at <https://aerobasegroup.com/nsn/5930-00-519-8144>

Thread Class:

2b

Body Style:

Hole mounted

Overall Length:

2.035 inches

Overall Height:

1.640 inches

Overall Width:

0.520 inches

Body Length:

1.660 inches

Body Width:

0.520 inches

Body Height:

1.300 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 125.0 dc

End Application:

Missminuteman leg-30

Inclosure Type:

Uninclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

0.172 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 100.000 milliamperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Test Data Document:

81349-mil-prf 8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 tab w/screw

Specification Data:

81349-mil-prf 8805/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0

Mil-std (military Standard):

spec.