NSN 5930-00-520-4825

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-520-4825

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

7.191 inches

Overall Height:

3.000 inches

Overall Width:

2.500 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.560 inches 2nd actuator

Individual Section Quantity:

14

Switch Contact Basic Design:

Nonpile-up nonsymmetrical and nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

31.0 dc at sea level

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

995.0 milliamperes resistive load dc at sea level

Special Features:

First shaft operates three wafers four poles twentyfour positions and ten single pole double throw switches; second shaft operates one wafer

two poles four positions

Precious Material And Location:

Contacts silver

Precious Material:

Silver

NSN 5930-00-520-4825

Rotary Switch - Page 2 of 2

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

