

View Online at <https://aerobasegroup.com/nsn/5930-00-520-5398>

Thread Class:

3a single pressure connection

Overall Length:

4.750 inches

Outside Diameter:

0.438 inches single connection

Overall Height:

1.500 inches

Overall Width:

1.500 inches

Body Length:

3.195 inches

Unthreaded Mounting Hole Diameter:

Between 0.200 inches and 0.206 inches

Distance Between Mounting Facility Centers:

1.120 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -34.0 degrees celsius and 74.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

6000.00 pounds per square inch gage

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

3675.00 actuation point pounds per square inch gage and 3825.00 actuation point pounds per square inch gage and 3000.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Swivel, plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0