NSN 5930-00-520-5817

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-520-5817

Thread Class:

2a single mounting facility

Thread Length:

0.340 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.310 inches

First Flat Length:

0.250 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.780 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Criticality Code Justification:

Feat

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

NSN 5930-00-520-5817

Rotary Switch - Page 2 of 2



Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Special Features:
Weapon system essential
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0