## NSN 5930-00-520-5817

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-520-5817

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.340 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

2.310 inches

First Flat Length:

0.250 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.780 inches single actuator

**Overall Diameter:** 

2.000 inches

**Individual Section Quantity:** 

2

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Shaft Type:** 

Round, flatted, threaded hole single actuator

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Screw

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-00-520-5817

Rotary Switch - Page 2 of 2



Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Special Features:
Weapon system essential
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0