

View Online at <https://aerobasegroup.com/nsn/5930-00-520-9353>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

0.750 inches

**Bushing Length:**

0.750 inches

**Body Length:**

1.090 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.500 amperes inductive dc and 2.500 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 2.500 amperes lamp ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0