

View Online at <https://aerobasegroup.com/nsn/5930-00-522-3362>

Hazardous Locations/environmental Protection:

Gastight

Overall Length:

1.217 inches

Overall Height:

0.500 inches

Body Diameter:

0.572 inches

Mounting Slot Width:

Between 0.133 inches and 0.147 inches

Body Height:

0.364 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.147 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Temperature Sensing Element Type:

Disc

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

160.00 actuation point degrees fahrenheit and 170.00 actuation point degrees fahrenheit and 151.00 deactuation point degrees fahrenheit and 161.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level fourth voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0