NSN 5930-00-522-3625

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-522-3625 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 1.656 inches **Overall Height:** Between 0.750 inches and 1.000 inches **Overall Width:** Between 0.750 inches and 1.000 inches **Body Diameter:** Between 0.750 inches and 1.000 inches **Bushing Length:** 0.406 inches **Body Length:** 0.969 inches **Actuator Diameter:** 0.234 inches **Actuator Height:** 0.312 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 8.000 amperes resistive dc and 2.000 amperes inductive dc and 2.000 amperes lamp dc **Thread Series Designator:** Uns **Terminal Type And Quantity:**

2 wire lead

NSN 5930-00-522-3625

Push Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0