

View Online at <https://aerobasegroup.com/nsn/5930-00-522-7050>

**Thread Class:**

2a

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.572 inches

**Body Length:**

1.125 inches

**Body Width:**

0.688 inches

**Body Height:**

0.770 inches

**Actuator Length:**

1.000 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.335 inches

**Actuator Width:**

0.687 inches

**Actuator Position-action Relationship:**

Left position momentary and right position momentary

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

27.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 15.000 amperes lamp dc

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0