## NSN 5930-00-524-2150

Thermostatic Switch - Page 1 of 2

120.0 ac at sea level single voltage



View Online at https://aerobasegroup.com/nsn/5930-00-524-2150

Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
2.812 inches
Overall Height:
1.500 inches
Overall Width:
0.656 inches
Mounting Slot Width:
0.156 inches
Body Length:
2.156 inches
Body Width:
0.656 inches
Body Height:
0.515 inches
Distance Between Mounting Facility Centers:
2.438 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Clamp and slot
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Threaded stud
Contact Load Current Rating:
10.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+50.00/+300.00 actuation point degrees fahrenheit and +45.00/+295.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
80.00 actuation point degrees fahrenheit and 75.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:

## **NSN 5930-00-524-2150** Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Rectangular w/bracket
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0