NSN 5930-00-525-0482

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-525-0482

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Round

- Actuator Diameter:
- 0.110 inches

Actuator Height:

0.167 inches

Actuator Free Position Height:

0.178 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 16.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

Special Features:

Contact assembly included with the switch

NSN 5930-00-525-0482

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0