

View Online at <https://aerobasegroup.com/nsn/5930-00-525-1806>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.200 inches

**Body Width:**

0.281 inches

**Body Height:**

0.825 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.093 inches and 0.096 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.625 inches

**Actuator Style:**

Round

**Actuator Free Position Height:**

0.234 inches

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

Between 3.0 ounces and 5.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0